ASSOCIATION CONNECTING ELECTRONICS INDUSTRIES®	© Co	terial Compo pyright 2005. IPC, Bannoc nternational and Pan-Ameri	kburn, Illinois	. All rights reserv	tion with lower	level p	arts, the	declaratio	n encom	passes all		naterials fo	r which th	e item is an assembly ne manufacturer has leclaration.
1752-2 1.1	IPC Web Site for Information on IPC-1752 Standard http://www.ipc.org/IPC-175x						Form Type * Declaration Class * Distribute Class 6 - RoHS Yes/No, Homogeneous Mate						Materials	and Mfg Informa
Supplier Information														
Company Name *		Company Unique ID		Unique ID Au	uthority	Respo	nse Date	*	R	esponse [Document ID			
SEMTECH CORPORATION	NC	SEMTECH CORPOR	RATION			2016-1	0-11							
Contact Name *		Title - Contact		Phone - Contact *		Email - Contact *				5 "				:
Elvia Finkel		Specialist, Document Control/C		805-498-2111		efinkel@semtech.com				Duplio	cate Conta	ct -> Auth	orized Re	presentative
Authorized Representative * Title - Representative			Э	Phone - Rep	Email - Representative *			* S	Supplier Comments or URL for Additional Information					
Elvia Finkel		Specialist, Documen	t Control/C	805-498-211	1	efinke	l@semte	ch.com						
Requester Item Number		Mfr Item Number		Mfr Item Name	Mfr Item Name		e Date	Version Manut		facturing Site Weig		* U	ОМ	Unit Type
		GN25L95C-QFN-TR		125Mb/s to 3	ırs			Taiwan		30		g	Each	
Alternate Recommend	ation				Alternate Item Co			Item Com	nments					
Manufacturing Proces	ss In	formation												
Terminal Plating / Grid Array	Mater	ial	Terminal Ba	ase Alloy	J-STD-020 MSL Ra	ating	Peak Proc	ess Body	Temperat	ture Max T	ime at Peak T	emperature	Number	of Reflow Cycles
Nickel/Palladium/Gold (Ni/Pd/Au) CU Alloy			,	1		260 (30 seconds 3				
Comments GN25L95C-QFN-TR is R	EACH	I-compliant product	, per EU R	Regulation E0	C1907/2006 to inc	lude re	cent add	ition of	SVHC ca	andidate l	ist of substa	ances in J	une 2016	;

Save the fields in Import fields from a Clear all of the Lock the fields on this **Export Data** Import Data Reset Form Lock Supplier Fields this form to a file file into this form fields on this form form to prevent changes **RoHS Material Composition Declaration Declaration Type *** Detailed Rohs Directive Rohs Definition: Quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury, Hexavalent Chromium, Polybrominated Biphenvls (PBB). Polybrominated Diphenyl Ethers (PBDE) and quantity limit of 0.01% by mass (100 PPM) of homogeneous material for Cadmium 2002/95/EC Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2002/95/EC and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a ?RoHS restricted substance?) in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance in excess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its suppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusive source of the Supplier?s liability and the Company?s remedies for issues that arise regarding information the Supplier provides in this form. In the absence of such written agreement, the warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply. 1 - Item(s) does not contain RoHS restricted substances per the definition above Supplier Acceptance * Accepted **RoHS Declaration *** Exemptions: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions. **Declaration Signature**

Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.

Supplier Digital Signature

Homogeneous Material Composition Declaration for Electronic Products

Subltem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Line Functions: +I Inserts a New Item /SubItem +M Inserts a new Material +C Inserts a new Substance Category +S Inserts a new Substance - Deletes the element line

Item/SubItem		Homogeneo	Homogeneous	NA/a i ada 4	Unit of		Level	Substance Category			Cubatanas	CAS	F	VA/a : a la t	Unit of	Toleranc	e DDM
	Name		Material	Weight	Measure		Level	Substance Category			Substance	CAS	Exempt	Weight	Measure	- +	PPM
+1 -1	Die	+M -M		1.62	mg	+C -C	Supplier		+S	-S	Si	7440-21-3		1.60623	mg		991,50
									+S	-S	Boron, Phosphorous	7440-42-8, 7		0.00016	mg		100
									+S	-S	Aluminium, Tungsten, (7429-90-5, 7		0.01361	mg		8,400
+1 -1	Lead Frame	+M -M	A194	9.6	mg	+C -C	Supplier		+S	-s	Copper	7440-50-8		9.22368	mg		960,80
									+S	-S	Iron	7439-89-6		0.21888	mg		22,800
									+S	-S	Zinc	7440-66-6		0.0144	mg		1,500
							_		+S	-S	Phosphorous	7723-14-0		0.00288	mg		300
						+C -C	В		+S	-S	Nickel	7440-02-0		0.13248	mg		13,800
						+C -C	Supplier		+S	-s	Palldium	7440-05-3		0.00576	mg		600
	_							,	+S	-s	Gold	7440-57-5		0.00192	mg		200
+1 -1	Die Attach	+M -M	1076DJ-G	0.024	mg	+C -C	Supplier		+S	-S	Silver	7440-22-4		0.01824	mg		760,00
									+S	-S	Epoxy Resin A	9003-36-5		0.00072	mg		30,000
									+S	-S	Epoxy Resin B	Trade Secre		0.00168	mg		70,000
									+S	-S	Hardener	Trade Secre		0.00072	mg		30,000
									+S	-S	Diluent A	Trade Secre		0.00072	mg		30,000
									+S	-S	Diluent B	Trade Secre		0.00168	mg		70,000
									+S	-S	Dicyandiamide	461-58-5		0.00007	mg		3,000
									+S	-S	Organic peroxide	Trade Secre		0.00017	mg		7,000
+1 -1	Wire	+M -M		0.03	mg	+C -C	Supplier		+S	-S	Copper	7440-50-8		0.02919	mg		973,00
	_	1						,	+S	-S	Palladium	7440-05-3		0.00081	mg		27,000
+1 -1	Mold Compound	+M -M	G700HA	18.726	mg	+C -C	Supplier		+S	-S	Epoxy Resin	Trade Secre	!	1.12356	mg		60,000
									+S	-S	Phenol Resin	Trade Secre		0.56178	mg		30,000
									+S	-S	Silica(Amorphous) A	60676-86-0		14.9808	mg		800,00

+S	-S	Silica (Amorphous) B	7631-86-9	1.8726	mg		100,00	
٠S	-S	Carbon Black	1333-86-4	0.18726	mg		10,000	