ASSOCIATION CONNECTING ELECTRONICS INDUSTRIES®	© Co	terial Compo pyright 2005. IPC, Bannoc international and Pan-Ameri	kburn, Illinois	. All rights reserv	tion with lower	level p	arts, the	declaratio		ses all lowe	er level mat	erials for	which th	item is an assembly e manufacturer has eclaration.	
1752-2 1.1	1.1 IPC Web Site for Information on IPC-1752 Standard http://www.ipc.org/IPC-175x						n Type * ribute	Declaration Class 6 - Ro	o, Homoge	Homogeneous Materials and Mfg Informat					
Supplier Information															
Company Name *		Company Unique ID		Unique ID Au	uthority	Respo	nse Date	*	Res	onse Doci	ument ID				
SEMTECH CORPORATION	SEMTECH CORPOR	RATION				2016-06-29									
Contact Name *	Title - Contact		Phone - Con	Email - Contact *											
Elvia Finkel		Specialist, Documen	t Control/C	805-498-2111		efinkel@semtech.com				Duplicate	Contact	-> Autho	rized Re	presentative	
Authorized Representative * Title - Representative			е	Phone - Representative *			Email - Representative *			Supplier Comments or URL for Additional Information					
Elvia Finkel		Specialist, Documen	t Control/C	805-498-211	1	efinke	l@semte	ch.com							
Requester Item Number	r	Mfr Item Number		Mfr Item Name)	Effectiv	e Date	Version	Manufacturi	ng Site	Weight *	UC	DM	Unit Type	
	GS2970AIBE3		3Gb/s, HD, SD SDI Receiver Co		•			Korea	390.792		mg	ıq	Each		
Alternate Recommenda	ation							Alternate	Item Comme	ents				<u> </u>	
Manufacturing Proces	ss In	formation													
Terminal Plating / Grid Array	Mater	ial	Terminal B	ase Alloy	J-STD-020 MSL Ra	ating	Peak Proc	ess Body	Temperature	Max Time	at Peak Tem	perature	Number o	of Reflow Cycles	
Tin/Silver/Copper (Sn/Ag/Cu) CU Alloy				3		260 (30 seconds 3						
Comments GS2970AIBE3 is a REAC	Н-со	empliant product, pe	r EU Regu	ılation EC190	07/2006 to include	e recer	nt addition	n of SVH	IC candida	te list of su	ubstances	Decemb	er 2015		

Save the fields in Import fields from a Clear all of the Lock the fields on this **Export Data** Import Data Reset Form Lock Supplier Fields this form to a file file into this form fields on this form form to prevent changes **RoHS Material Composition Declaration Declaration Type *** Detailed Rohs Directive Rohs Definition: Quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury, Hexavalent Chromium, Polybrominated Biphenvls (PBB). Polybrominated Diphenyl Ethers (PBDE) and quantity limit of 0.01% by mass (100 PPM) of homogeneous material for Cadmium 2002/95/EC Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2002/95/EC and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a ?RoHS restricted substance?) in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance in excess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its suppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusive source of the Supplier?s liability and the Company?s remedies for issues that arise regarding information the Supplier provides in this form. In the absence of such written agreement, the warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply. 1 - Item(s) does not contain RoHS restricted substances per the definition above Supplier Acceptance * Accepted **RoHS Declaration *** Exemptions: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions. **Declaration Signature**

Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.

Supplier Digital Signature

Homogeneous Material Composition Declaration for Electronic Products

Subltem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Line Functions: +I Inserts a New Item /SubItem +M Inserts a new Material +C Inserts a new Substance Category +S Inserts a new Substance - Deletes the element line

	Item/SubItem		Homogeneous	VA/ a i aula 4	Unit of		Laval	Substance Cotemani		Substance	CAS	F	Mainht	Unit of	Tolerance		PPM	
	Name		Material	Weight	Measure		Level	Substance Category			Substance	CAS	Exempt	Weight	Measure	-	+	PPW
+1 -1	Substrate	+M -M	вт	159.84	mg	+C -C	Supplier		+S	-S	SiO2	60676-86-0		17.023	mg			106,50
									+S	-s	Acrylic	Proprietary		15.984	mg			100,00
									+S	-s	Ероху	Proprietary		12.787	mg			80,000
									+S	-s	Bisphenol	Proprietary		23.976	mg			150,00
									+S	-s	Triazol	Proprietary		27.972	mg			1,750,0
									+S	-s	Cu	7440-50-8		58.821	mg			368,00
						+C -C	В		+S	-s	Nickel	7440-02-0		2.398	mg			15,000
						+C -C	Supplier		+S	-s	Au	7440-57-5		0.879	mg)	5,500
+1 -1	Mold Compound	+M -M	KE-G1250	159.24	mg	+C -C	Supplier		+S	-S	Silica (fused)	60676-86-0		140.131	mg		,	880,00
	_		-				-		+S	-s	Epoxy Resin	Proprietary		9.554	mg			60,000
									+S	-s	Phenolic Resin	Proprietary		8.758	mg			55,000
									+S	-s	Carbon Black	1333-86-4		0.796	mg			5,000
+1 -1	Chip	+M -M		12.54	mg	+C -C	Supplier		+S	-S	Si	7440-21-3		12.377	mg			987,00
			-				-		+S	-s	AI	7429-90-5		0.075	mg			6,000
									+S	-s	w	7440-33-7		0.05	mg			4,000
									+S	-s	Ti	7440-32-6		0.038	mg			3,000
+1 -1	Die Attach	+M -M	2100A	6.874	mg	+C -C	Supplier		+S	-S	Ag	7440-22-4		5.293	mg			770,00
	_		-				-		+S	-s	Epoxy Resin	Proprietary		0.447	mg			65,000
									+S	-s	Functionalized Resin	Proprietary		0.447	mg			65,000
									+S	-s	Diester	Proprietary		0.687	mg			100,00
+1 -1	Wire	+M -M		3.658	mg	+C -C	Supplier		+S	-s	Au	7440-57-5		3.658	mg			999,90
+1 -1	Solder Balls	+M -M		48.64	mg	+C -C	Supplier		+S	ş	Sn	7440-31-5		46.938	mg			965,00
									+S	-s	Ag	7440-22-4		1.459	mg			30,000

+S	-s	Cu	7440-50-8	0.243	mg		5,000	
					_			