ASSOCIATION CONNECTING ELECTRONICS INDUSTRIES ®	© Co	terial Compo pyright 2005. IPC, Bannoc nternational and Pan-Ameri	kburn, Illinois	. All rights reserve	tion with lower	level p	arts, the	declaratio	n encom		ver level mat	erials for	which th	item is an assembly e manufacturer has eclaration.		
1752-2 1.1	•	Web Site for Informat		n Type * ribute	-	Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materials and Mfg Informat										
Supplier Information																
Company Name *	Company Unique ID		Unique ID Au	Response Date *			F	Response Document ID								
SEMTECH CORPORATION		SEMTECH CORPOR	RATION		2012-06-27											
Contact Name *		Title - Contact		Phone - Con	Email - Contact *				<b>D</b> !: .	<u> </u>	A .1	5				
ROYA READER		QUALITY ASSURAN	ICE CUST	805-389-274	rreader@semtech.com				Duplicat	e Contact	-> Autho	orized Re	presentative			
Authorized Representative *		Title - Representative	е	Phone - Rep	Email - Representative *			* 5	Supplier Comments or URL for Additional Information							
ROYA READER	QUALITY ASSURAN	NCE CUST	805-389-274	rreader@semtech.com												
Requester Item Number		Mfr Item Number		Mfr Item Name	Effectiv	e Date	Version	Manufac	cturing Site	Weight *	UC	OM	Unit Type			
		RClamp7524T.TNT		Ultra Low Cap	а			China		1.184	mg	3	Each			
Alternate Recommenda	ation						Alternate I			em Comments						
Manufacturing Proces	ss In	formation														
Terminal Plating / Grid Array Material			Terminal Base Alloy		J-STD-020 MSL Rating		Peak Process Body Temp		Tempera	ture Max Tim	e at Peak Tem	Peak Temperature		of Reflow Cycles		
Nickel/Palladium/Gold (Ni/Pd/Au)			CU Alloy		1			<b>260</b> C			<b>30</b> s	30 seconds				
Comments  RClamp7524T.TNT is RE	EACH	I-compliant product	, per EU R	egulation EC	1907/2006 to inc	lude re	ecent add	lition of S	SVHC c	andidate list	of substance	ces in Ju	ıne 2012			

Save the fields in Import fields from a Clear all of the Lock the fields on this **Export Data** Import Data Reset Form Lock Supplier Fields this form to a file file into this form fields on this form form to prevent changes **RoHS Material Composition Declaration Declaration Type \*** Detailed Rohs Directive Rohs Definition: Quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury, Hexavalent Chromium, Polybrominated Biphenvls (PBB). Polybrominated Diphenyl Ethers (PBDE) and quantity limit of 0.01% by mass (100 PPM) of homogeneous material for Cadmium 2002/95/EC Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2002/95/EC and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a ?RoHS restricted substance?) in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance in excess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its suppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusive source of the Supplier?s liability and the Company?s remedies for issues that arise regarding information the Supplier provides in this form. In the absence of such written agreement, the warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply. 1 - Item(s) does not contain RoHS restricted substances per the definition above Supplier Acceptance \* Accepted **RoHS Declaration \*** Exemptions: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions. **Declaration Signature** 

Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.

Supplier Digital Signature

## **Homogeneous Material Composition Declaration for Electronic Products**

**Subltem Instructions:** The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

**Substance Instructions:** [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Line Functions: +I Inserts a New Item /SubItem +M Inserts a new Material +C Inserts a new Substance Category +S Inserts a new Substance - Deletes the element line

	Item/SubItem		Homogeneous	Weight	Unit of			_evel	Substance Category			Substance	CAS	Exempt	Weight	Unit of Measure	Tolerance		PPM
	Name		Material	Weight	Measure			.0401	oubstance Category			Gubstance	OAO .	Lxcilipt			-	+	
+1 -	Die	+M -M	Doped Silicon	0.3302	mg	+C -	CSu	upplier		+S	-s	Si	7440-21-3		0.0288	mg			24,326
+1 -	Lead Frame	+M -M	C7025	0.41277	6mg	+C -	CSI	upplier		+S	-S	Cu	7440-50-8		0.3959	mg			334,35
	_									+S	-S	Si	7440-21-3		0.003	mg			2,528
						+C -	СВ		Nickel (external applic	+S	-S	Nickel	7440-02-0		0.0132	mg			11,157
						+C -	C Sı	upplier		+S	-S	Mg	7439-95-4		0.0007	mg			610
		+M -M	Ni/Pd/Au plating	0.01058	4mg	+C -	СВ			+S	-S	Nickel	7440-02-0		0.0095	mg			8,061
						+C -	CS	upplier	middle plating	+S	-S	Pd	7440-05-3		0.0009	mg			733
						+C -	CS	upplier	outer plating	+S	-S	Au	7440-57-5		0.0002	mg			146
+1 -	Bonding wire	+M -M	Gold wire	0.0115	mg	+C -	CSI	upplier		+S	-s	Au	7440-57-5		0.0115	mg			9,719
+1 -	Molding Compound	+M -M	EME-G770HCD	0.70437	4mg	+C -	C Sı	upplier		+S	-s	Silica fused	60676-86-0		0.6586	mg			556,27
		•	_							+S	-S	Epoxy resin	Proprietary		0.0211	mg			17,848
										+S	-S	Phenol resin	Proprietary		0.0211	mg			17,848
										+S	-S	Carbon Black	1333-86-4		0.0035	mg			2,975
+1 -	Die attached Epoxy	+M -M	QMI519	0.01589	3mg	+C -	CSI	upplier		+S	-s	Ag	7440-22-4		0.0127	mg			10,739
	-		•	•	•					+S	-S	Palladium compound	Proprietary		0.00002	mg			20
										+S	-S	2,6-Di-tert-butyl-p-creso	128-37-0		0.000001	mg			1
										+S	-S	Hydroquinone	123-31-9		0.000000	mg			0.009
										+S	-\$	Acrylate	Proprietary		0.025	mg			2,127
										+S	-S	Bismaleimide resin	Proprietary		0.0005	mg			403
										+S	-S	Polymer of polybutadie	Proprietary		0.0002	mg			134