ASSOCIATION CONNECTING ELECTRONICS INDUSTRIES®	© Co	terial Compo pyright 2005. IPC, Bannoc nternational and Pan-Ameri	kburn, Illinois	. All rights reserve	tion with lower	level p	arts, the	declaration	n encor		er level mate	erials for	which th	item is an assembly e manufacturer has eclaration.		
1752-2 1.1	IPC Web Site for Information on IPC-1752 Standard http://www.ipc.org/IPC-175x						n Type * ibute	-		ation Class * 6 - RoHS Yes/No, Homogeneous Materials and Mfg Informat						
Supplier Information																
Company Name *	Company Unique ID		Unique ID Au	Response Date *				Response Document ID								
SEMTECH CORPORATION		SEMTECH CORPOR	RATION		2012-06-08											
Contact Name *		Title - Contact		Phone - Contact *		Email - Contact *				5 " .	2	A (1		1		
ROYA READER		Quality Assurance C	805-389-274	05-389-2742		rreader@semtech.com			Duplicate	Contact	-> Autho	rized Re	presentative			
Authorized Representative *		Title - Representative	Phone - Rep	Phone - Representative *		Email - Representative *			Supplier Comments or URL for Additional Information							
ROYA READER	Quality Assurance C	ustomer S	& 05-389-274	-389-2742 r		rreader@semtech.com										
Requester Item Number		Mfr Item Number		Mfr Item Name		Effective Date		Version Manufa		cturing Site	Weight *	UC	M	Unit Type		
		SC2618SKTRT		Miniature PW	u			Malays	ia	12.3165	mg	J	Each			
Alternate Recommenda	ation				Alternate Item Co			omments								
Manufacturing Proces	ss In	formation														
Terminal Plating / Grid Array Material			Terminal B	ase Alloy	J-STD-020 MSL Rating		Peak Process Body Tempe		Temper	rature Max Time at Peak Tem		perature	perature Number of Reflow C			
Nickel/Palladium/Gold (Ni/Pd/Au)		CU Alloy		1				260 C		30 seco		ds 3				
Comments SC2618SKTRT is REAC	H-cor	mpliant product, pe	r EU Regu	lation EC190	7/2006 to include	recent	t additior	n of SVH	C cand	idate list of su	ıbstances i	n Febru	ary 2012			

Save the fields in Import fields from a Clear all of the Lock the fields on this **Export Data** Import Data Reset Form Lock Supplier Fields this form to a file file into this form fields on this form form to prevent changes **RoHS Material Composition Declaration Declaration Type *** Detailed Rohs Directive Rohs Definition: Quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury, Hexavalent Chromium, Polybrominated Biphenvls (PBB). Polybrominated Diphenyl Ethers (PBDE) and quantity limit of 0.01% by mass (100 PPM) of homogeneous material for Cadmium 2002/95/EC Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2002/95/EC and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a ?RoHS restricted substance?) in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance in excess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its suppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusive source of the Supplier?s liability and the Company?s remedies for issues that arise regarding information the Supplier provides in this form. In the absence of such written agreement, the warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply. 1 - Item(s) does not contain RoHS restricted substances per the definition above Supplier Acceptance * Accepted **RoHS Declaration *** Exemptions: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions. **Declaration Signature**

Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.

Supplier Digital Signature

Homogeneous Material Composition Declaration for Electronic Products

Subltem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Line Functions: +I Inserts a New Item /SubItem +M Inserts a new Material +C Inserts a new Substance Category +S Inserts a new Substance - Deletes the element line

	Item/SubItem		Homogeneous	Weight	Unit of		Lavel	Substance Cotegory			Substance	CAS	Evempt	Woight	Unit of	Tolerance		PPM
	Name		Material	weight	Measure		Level	Substance Category			Substance	CAS	Exempt	Weight	Measure	-	+ '	PPIVI
+1 -	Die	+M -M	Doped Silicon	0.8	mg	+C -C	Supplier		+S	-S	Si	7440-21-3		0.8	mg		6	64,953
+1 -	Leadframe	+M -M	C194	4.7	mg	+C -C	Supplier		+S	-S	Copper	7440-50-8		4.53973	mg		3	68,58
									+S	-S	Iron	7439-89-6		0.10603	mg		8	3,608.9
						+C -C	A	Lead/Lead Compound	+S	-S	Lead	7439-92-1		0.00014	mg		1	11.45
						+C -C	Supplier		+S	-S	Phosphorus	7723-14-0		0.00113	mg		9	91.58
									+S	-S	Zinc	7440-66-6		0.00597	mg		4	484.63
						+C -C	Supplier	Silver plating	+S	-S	Ag	7440-22-4		0.047	mg		3	3,816.0
+1 -	Die attach material	+M -M	QMI519	0.07	mg	+C -C	Supplier		+S	-S	Ag	7440-22-4		0.06	mg		4	,575.1
									+S	-S	Carbocyclic Acrylates	Proprietary		0.01	mg		5	568.34
									+S	-S	Bismaleimide resin	Proprietary		0.002	mg		1	170.5
									+S	-S	2-preponoic acid, 2-met	68586-19-6		0.002	mg		1	170.5
									+S	-S	additive	Proprietary		0.002	mg		1	170.5
									+S	-S	Dicumlyl peroxide	80-43-3		0.0004	mg		2	28.42
+1 -	Bonding wire	+M -M	Gold wire	0.17	mg	+C -C	Supplier		+S	-S	Au	7440-57-5		0.17	mg		1:	3,802
+1 -	Encapsulation	+M -M	CEL8240HF10	5.94	mg	+C -C	Supplier		+S	-S	Epoxy Resin-1	Proprietary		0.18	mg		1.	4,468
									+S	-S	Epoxy Resin-2	Proprietary		0.18	mg		1	14,468
									+S	-S	Phenol resin	Proprietary		0.27	mg		2	21,702
									+S	-S	Silica	60676-86-0		5.19	mg		4	421,03
									+S	-S	Carbon Black	1333-86-4		0.01	mg		9	964.56
	<u> </u>								+S	-S	Others	Proprietary		0.12	mg		9	9,645.6
+1 -	Lead Finish	+M -M	Tin Alloy	0.6365	mg	+C -C	Supplier		+S	-S	Sn	7440-31-5		0.54	mg		4:	13,926
						+C -C	A	Lead/Lead Compound	+S	-S	Lead	7439-92-1		0.09548	mg		7	7,751.8